



General Purpose

- Suitable for general cargo
- Floor height approx. 170mm
- Lashing rings on internal sides
- Lashing devise load approx. 1000kg each

Type	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Capacity	Tare Weight	Maximum Pay-load
20'	5898mm	2352mm	2392mm	2338mm	2280mm	33.2m3	2185kg	28,295kg
40'	12,032mm	2350mm	2390mm	2338mm	2280mm	67.6m3	3845kg	26,635kg



High Cube

- Designed for voluminous cargo up to 2.70m high
- Floor height approx. 170mm
- Lashing rings on internal sides
- Lashing devise load approx. 1000kg each
- NOTE: consider over-height for inland transportation

Type	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Capacity	Tare Weight	Maximum Pay-load
40'	12,032mm	2350mm	2695mm	2338mm	2585mm	76.2m3	4015kg	26,465kg



Open Top

- Designed for cargo loaded from door or top side (e.g. by crane)
- Covered by tarpaulin
- Floor height approx. 170mm
- Lashing rings on internal sides
- Lashing devise load approx. 1000kg each


Type	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Capacity	Tare Weight	Maximum Pay-load
20'	5894mm	2346mm	2352mm	2342mm	2281mm	32.5m3	2230kg	28,250kg
40'	12,029mm	2352mm	2348mm	2340mm	2280mm	65.9m3	3920kg	26,560kg



Flat Rack

- Designed for heavy loads and oversized cargo
- Also available as collapsible Flat Rack, usually with spring assisted end walls
- Lashing points on corner posts, rails and floor
- Lashing devices load approx. 5000kg each

Type	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Capacity	Tare Weight	Maximum Pay-load
20'	6038mm	2438mm	2213mm	----mm	----mm	Variable	2740kg	31,260kg
40'	12,080mm	2438mm	1955mm	----mm	----mm	variable	4900kg	40,100kg



Reefer Container

- Designed to transport goods requiring temperature-control
- Suitable for fruit, vegetables, dairy and meat
- Refrigeration unit connected to ships electrical supply

Type	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Capacity	Tare Weight	Maximum Pay-load
20'	5440mm	2290mm	2270mm	2230mm	2100mm	28.3m3	3080kg	27,400kg
40'	11,560mm	2280mm	2250mm	2290mm	2260mm	59.3m3	4800kg	27,700kg